

# WS 1720 RR ESD



## Design

### Material

Seat / Backrest	imitation leather / imitation leather
Five star base xx20 Ø655mm with dual castors (Ø 65mm)	diecast aluminium unloaded braked - loaded unbraked
Column xx20	safety gas spring, chrome plated, with column cover
Backrest steel bar	high-precision steel bar, Ø100 x 26mm

Total height *	960 to 1220mm
----------------	---------------

Thickness of seat / backrest *	95mm / 115mm
--------------------------------	--------------

Weight *	18.20kg
----------	---------

Loading capacity	120kg
------------------	-------

## Adjustabilities

Seat height (acc. DIN 68877) *	510 to 630mm
Seat tilt *	-6° to +8°
Seat lock	continuous
Backrest tilt *	-6° to +8°

### Backrest

Width top / bottom *	340 / 455mm
Height *	520mm

### Seat

Width front / back *	510 / 480mm
Depth *	470mm

\*production or model related differences are possible

## Characteristics

Conductivity	10 <sup>4</sup> Ohm to 10 <sup>6</sup> Ohm acc. BS EN 61340-5-1:2007
--------------	--

Certified for class-5 clean rooms according to the DIN EN ISO 14644-1 standard.

Werksitz imitation leather is urine, blood and sweat resistant in accordance with the DIN 53160 standard.

Revision status	11.02.2015
-----------------	------------

**WS 1720 RR ESD**



**Fraunhofer**  
IBMT



\*: The illustrated product may show accessories with surcharge.

